

Link do produktu: <http://store.electroinstall.pl/zestaw-glosnikowy-serii-vxs-vxs1mlw-yamaha-p-1565.html>

Zestaw głośnikowy serii VXS YAMAHA

Cena	349,00 zł
Dostępność	Na zamówienie
Czas wysyłki	7-10 dni
Numer katalogowy	VXS1MLW
Producent	YAMAHA

Opis produktu

Optimized for Background Music

Background music reproduction requires uniform dispersion, uniform frequency response, and optimum sound pressure level for the space. The VXS Series M model has been designed specifically for BGM applications, and satisfies all of the above conditions to the highest degree. Broad 170° horizontal and vertical dispersion delivers uniformly accurate frequency response throughout the coverage area, providing sound so natural that the listener might be fooled into believing it is a live musical performance.

High-performance Full-range Driver

The VXS1ML features a newly developed compact 1.5-inch full-range driver with a powerful neodymium magnet. This innovative driver has been painstakingly designed to achieve remarkably detailed, realistic reproduction of musical waveforms. The entire system has been fine-tuned to deliver top-quality sound in a surprisingly compact, lightweight unit.

A Sublime Blend of Function and Elegance

In addition to being packed into the smallest possible dimensions to minimize visual impact, the VXS1ML boasts smoothly flowing lines that allow it to blend unobtrusively with just about any interior décor. The VXS1ML brings together the best of both worlds: outstanding sound and sophisticated visual appeal.

Mounting Options for Any Interior

The VXS series M model is prepared many type of brackets, and corresponds to various installation according to the application.

Included bracket

The VXS series M model is supplied with hardware for easy wall and ceiling surface mounting.

Ceiling mound adapter

Optional CMA1MB and CMA1MW ceiling mount adapters are available for flush ceiling or wall installation that makes the speakers even less visible.

Rail mount adapter

Optional RMA1MB rail mount adapter that allows spotlight-like mounting on a lighting rail.

* Referring to the illustration below, the RMA1MB can be used with lighting rails in which dimension A is greater than 1.5mm and less than 6.0mm, and dimension B is greater than 3mm.

Specyfikacja

Speaker type		Full-range, acoustic suspension type
Frequency range (-10dB)		180Hz-20kHz
Nominal coverage	H	170°
	V	170°
Components	LF-HF	1.5" Cone
Power rating	NOISE	5W
	PGM	10W
	PEAK	20W
Nominal impedance		8Ω
SPL	Sensitivity (1W; 1m on axis)	79dB SPL *1
	Peak (Calculated)	92dB SPL *2
I/O connectors		Euroblock (2 pin) × 1
Finish		VXS1MLB: Black (approximate value: Munsell N3), VXS1MLW: White (approximate value: Munsell N9)
Dimensions	W	62mm (2.4") *3
	H	62mm (2.4") *3
	D	82mm (3.2") *3
Net weight		0.17 kg (0.37 lbs) *3
Accessories		Wall/Ceiling Bracket
Packaging		Packaged each
Certificate		NFPA70, CE, RoHS

- *1: Full-space (4π) (300Hz-10kHz)
- *2: Calculated based on power rating and sensitivity, exclusive of power compression
- *3: Speaker only